



## FRONT FIBERGLASS FENDERS - FORD E-SERIES 1997-2007

**WARNING! READ ALL INSTRUCTIONS BEFORE BEGINNING INSTALLATION**  
**CONFIRM MEASUREMENTS BEFORE DRILLING ANY HOLES**

### PARTS LIST:

FRONT

**2** E-SERIES FIBERGLASS FENDERS

### TOOLS NEEDED:

FRONT:  
PHILIPSHEAD SCREWDRIVER  
FLATHEAD SCREWDRIVER  
8MM SOCKET/WRENCH  
10MM SOCKET/WRENCH  
1/2" SOCKET/WRENCH  
1/2" DRILL BIT  
5/16 DRILL BIT  
DRILL

**INSTALLATION INSTRUCTIONS**

**DISASSEMBLY**

**Helpful tip before you get started:**

Before you paint your new fiberglass fenders fit and install first then uninstall to have painted

**STEP 1:**

Unscrew two Phillips screws holding turn signals on both sides

Remove turn signals and make sure to unplug turn signals

**STEP 2:**

Remove the grill and headlights for easier access to bolts and fitting fenders

Remove plastic fasteners with a flat head screwdriver. Two metal tabs holding the headlights and 4 10mm bolts holding the grill in place

Now remove headlights and grill as one unit and don't forget to unplug headlights

**STEP 3:**

Remove all ten 10mm bolts holding the fender to the van

- 1) On top of fender next to engine bay: 3
- 2) Under bottom of fender: 1
- 3) Where turn signal sits : 2
- 4) In door jam: 2
- 5) Just above bumper: 2



**DISASSEMBLY****STEP 4:**

Use a 10mm wrench to unscrew antenna

Use a flat head screwdriver to pop off the plastic cover

Unplug the antenna and remove stock fender

**STEP 5:**

Test fit the new fiberglass fender

**STEP 6:**

Line up and drill 3 holes to match ones on the top side of the fender

Use 5/16 drill bit to leave room for adjustments

**\*Note: When tightening fiberglass make sure to not over tighten as the material may crack**



**DISASSEMBLY****STEP 7:**

Drill one hole at the bottom of the fender just above the bumper with a 5/16 drill bit

Use 5/16 inch hardware and 1/2 inch wrench/socket to tighten

For this portion only, reuse stock bolts

**STEP 8:**

Drill 1 5/16 hole at bottom of fender near wheel well

2 holes in door jam

2 holes where turn signal sits

Reinstall stock bolts for this portion

**STEP 9:**

Make sure to check gaps and that door doesn't rub against the fiberglass

Close the hood to make sure gap is sufficient

Readjusting a few times to get the perfect fitment might be necessary



**DISASSEMBLY****STEP 10:**

Drill one hole on each side with a 1/2" drill bit so the retaining tabs for the headlight/grill will seat properly

**STEP 11:**

Reinstall the headlight, turn signal and grill

Don't forget to plug the headlights back in before buttoning everything up

Your E-series fiberglass fender install is now complete

