



## OCOTILLO CRUISER KIT - 1992-2014 FORD E-SERIES

**WARNING! READ ALL INSTRUCTIONS BEFORE BEGINNING INSTALLATION**  
CONFIRM MEASUREMENTS BEFORE DRILLING ANY HOLES

### PARTS LIST:

- |  |                               |
|--|-------------------------------|
| <b>2</b> WTD – CUSTOM EXTENDED RADIUS ARMS       | <b>SHOCK HARDWARE</b>         |
| <b>2</b> WTD – RADIUS ARM BRACKETS (WELD ON)     | • ½" X 3" BOLT                |
| <b>MOOG RADIUS ARM PIVOT BUSHING KIT</b>         | • ½" FLAT WASHER              |
| • SLEEVE   | • ½" LOCK WASHER              |
| • FRONT CUPPED WASHER                            | • ½" NUTS                     |
| • FRONT ROUND BUSHING                            | <b>2</b> FORD E-SERIES UBOLTS |
| • SPACER RING                                    | <b>2</b> 2" BLOCKS            |
| • REAR CONCAVE BUSHING                           |                               |
| • LARGE WASHER                                   |                               |
| • LOCK WASHER                                    |                               |
| • NUT  |                               |
| <b>2</b> SKYJACKER LIFT COILS                    |                               |
| <b>2</b> MODIFIED I BEAMS W/ MOOG PIVOT BUSHINGS |                               |
| <b>4</b> FOX PERFORMANCE SERIES 2.0 SHOCK        |                               |

### TOOLS NEEDED:

- FRONT:**
- 10MM SOCKET
  - 15MM SOCKET
  - 18MM SOCKET
  - 19MM SOCKET
  - 21MM SOCKET
  - 30MM SOCKET
  - 1-1/8" SOCKET
- 3/8" AND/OR 1/2" RATCHET GRINDER W/ SANDING DISC**
- MIG WELDING MACHINE**
- TAPE MEASURER**
- SHARPIE**
- HAMMER**
- PLIERS**
- REAR:**
- 15MM SOCKET
  - 19MM SOCKET
  - 21MM SOCKET
  - 24MM DEEP SOCKET/WRENCH

**INSTALLATION INSTRUCTIONS**

## DISASSEMBLY

Be sure to measure ride height before and after install for a true measurement of the total height lifted. We recommend using a piece of blue painters' tape on the front and back fenders. To find the before measurement, take a tape measurer and measure from the ground to the bottom of the fender well lip. Write that measurement on the blue tape. This step will be repeated once the lift is installed.

### STEP 1:

Jack up front of van so the front wheels are off the ground and place jack stands under the frame behind the front bumper. This is for safety while you are completing the installation of this lift kit. Remove front wheels using a 22mm socket.



### STEP 2:

1993-2007:

Remove the sway bar from frame with a 15mm, pull sway bar from I beams.

2008-Current:

Remove sway bar from frame with 15mm and a 18mm. Using 15mm remove sway bar from sway bar links from I beams.



### STEP 3:

There is a cotter pin in the bottom of the steering castle nut. Using a pliers, bend the cotter pin into a straight position and then tap it out before loosening the nut. Now use a 21mm to remove the tie rod nut.

*Tip: Smack knuckle with large hammer to free up tie rod.*



## DISASSEMBLY

### STEP 4:

Undo the brake caliper with a 21mm and move it out of the way by hanging it on a hook to get clear access to the core of the suspension.

*Tip: Make a double-sided metal hook, loop one end to a hole in the frame, then hang the steering knuckle on the other end of the hook once you remove it.*

*Note: Stock brake lines do not need to be removed/replaced and bleeding the brakes is not necessary. Angling 90 degree fitting down will give you more length on your brake line.*



### STEP 5:

Make sure you have a jack supporting the suspension on the side you are working on. Now remove factory shock using a 21mm, then remove factory coil retainer on top of coil bucket using a 10mm.



### STEP 6:

Remove the eccentric bolt on top front of I beam with a 15mm, on bottom side of I beam, remove nut using a 1-1/8 wrench. Be sure to leave the nut threaded on finger tight to avoid injury or damage from the whole piece dropping. Once all hardware is removed from the steering knuckle, take a hammer and hit the main points of contact to loosen the assembly. Lastly, remove the lower nut you left on finger tight, allowing everything to be removed. Set the assembly off to the side in a position that does not put strain on the brake lines. Remove ABS wire from frame. Undo plug and detach from brake line. Curl up wire to avoid damage during removal of hub.



---

**DISASSEMBLY****STEP 7:**

Now that everything is taken off and the caliper, brakes and spindle are moved to the side. Using a 21mm socket on the top and a 30mm socket on the bottom, remove hardware to separate the I beam from the radius arm. We recommend placing a jack stand under the I beam to avoid it from dropping and causing injury.

**STEP 8:**

Using a 1-1/8", remove the stock radius arm pivot from mounting bracket. Now use 15mm to remove bracket from frame.

**STEP 9:**

Using a 19mm and a 21mm (1992 - 2007) or 21mm and a 21mm (2008 - 2014) unbolt where the I beam pivots on the frame

*Tip: The bolt for the passenger side I Beam is on the front side of the van facing the steering. Be sure to put it back the same way. If not done properly, the additional mount could hit the I beam when the I beam is moving up and down due to the additional length.*



*Note: Now that the front stock suspension is off, clean the frame and prep for the radius arm bracket installation. Start by sanding down the powder coating on the radius arm brackets at the points of contact which will be welded to the frame.*

## FRONT INSTALLATION (START ON DRIVER SIDE)

### STEP 10:

Radius arm assembly: Using the Moog bushing kit. We recommend putting everything together prior to installing it on the van.

Take the extended radius arm and place the hardware on the threaded end in this order:

- Sleeve
- Front Cupped Washer
- Front Round Bushing
- Spacer Ring
- Radius Arm Bracket (Lip end first)
- Rear Concave Bushing
- Large Washer
- Lock Washer
- Nut



Snug the assembly tight so everything interlocks with focus on the crush sleeve.

*Note: While installing the I beams, notice the passenger side I beam has a metal nub that will be pointing forward if installed correctly. Also notice that the I beams are two different lengths. The driver side will be the longer one.*



### STEP 11:

Starting with the passenger I Beam, take the stock bolt and insert it through the original factory hole from the back. Now repeat the same process on the other side. If there is resistance, wiggle the I beam to get the bolt through the hole.

**Radius Arm Bracket Relocation:**  
**Repeat Steps for Both Sides**



## FRONT INSTALLATION

### STEP 12:

Take a tape measurer and hook it on the inside lip of the back of the second body mount bracket (under driver/passenger feet) and mark at desired location depending on tire size.

33" Tires:

Measure 10" back on the frame

35" Tires:

Measure 9.5" - 9-3/8" back on the frame



### STEP 13:

Next, bolting the extended radius arm with mounting bracket to the I Beam using factory hardware. Place a jack stand under the I Beam to help support it while using a jack to position radius arm bracket flush on frame.

*Tip: Once the bracket is positioned correctly, use a C-clamp to clamp the radius arm bracket snug to the frame. Then check the measurement once more prior to welding.*




### STEP 14:



Welding the Radius Arm Bracket to the frame. Only weld the front and bottom of the bracket, not the back side.

**Weld Radius Arm Bracket to frame only on red areas.**

Front View



Back View



---

**FRONT END REASSEMBLY**

*Note: We recommend spraying WD40 on all the threads and insides of bolts prior to assembling. This will lubricate and help everything to go back together smoothly, especially on vehicles that have a lot of rust.*

**STEP 15:**

Tighten 30mm and 21mm going through radius arm and I beam and tighten 1-1/8" bolt on radius arm bracket hardware. Install spring isolator on top of radius arm bolt. Then install coil by replacing J-hook using 10mm.

**STEP 16:**

Install Fox 2.0 shock. Take the top nut, washer and bushing off the shock and then insert the shock up into the designated hole located on the right side of the coil bucket.

Put the remaining bushing and hardware on the top shock post, which is now exposed on the top side of the coil bucket and make it finger tight.

Then put a 19mm wrench on the top nut and twist the shock by hand until snug (do not overtighten shock bushings).

Using a floor jack, compress the coil spring so the lower shock bolt fits in the radius arm tabs using a 3/4" socket and wrench, tighten shock hardware.



## STOCK COMPONENT REASSEMBLY

### STEP 17:

Reassemble in the reverse order ALL factory parts which were removed. Put the hardware back on finger tight and then follow up with the wrench to avoid fighting the parts.



### STEP 18:

Now that your vehicle is assembled and sitting on the ground, loosen the tie rods with a 15mm, use channel locks to toe in tie rods to correct the steering.

*Note: Alignment shop will fine tune this adjustment as well as replace eccentric to correct camber and caster.*

*If there are rubbing issues with the front tires and the bumper, carefully mark and trim away to avoid potential tire damage.*

*If you don't have access to a welding machine, you can take your vehicle to a weld shop and have the brackets welded on per step 12. Once this is completed, continue your build.*



---

## REAR INSTALLATION - BLOCKS & U-BOLTS

### STEP 1:

Jack the back of the van up and remove rear tires.

Place jack stands under rear frame.

Remove the bolts from the bottom of the shock mounts with a 15mm and a 18mm (1992 - 2007) or a 19mm wrench and socket (2008 - 2014).



### STEP 2:

Remove upper shock nut using a 15mm, then remove rubber shock bushing from frame using a flathead screwdriver.



### STEP 3:

Place a second set of jack stands under the rear axle loosen u-bolts using a 24mm deep socket only on one side. On opposite side, remove u-bolts completely and use a floor jack to lower rear end to fit blocks.

*Note: If blocks have a taper in them, make sure the tall side goes towards rear of vehicle.*



## REAR INSTALLATION - BLOCKS & U-BOLTS

### STEP 4:

Align lift block with locating pin in axle and leaf spring, then install the longer u-bolts. When installing u-bolt nuts, only snug at this point. Now repeat steps on other side. Once you have both blocks in, tighten u-bolt nuts to 165 ft lbs.



### STEP 5:

While installing the new Fox 2.0 Shocks, remove the top nut, washer and bushing. Slide the top shock post into the designated stock hole where the old shock was removed and then reach over the frame to put the bushing, washer and nut on the post. Place wrench on the nut and turn the shock by hand until it is tight. Jack up rear end to align lower shock mounts with tabs and replace factory hardware.



Put the rear wheels and tires back on and lower the jacks.

Now take the tape measurer and measure from the ground to the bottom of the fender lip and write the new ride height on the blue painter's tape that was placed on the fenders before started the install. If everything was done correctly, a true 5 inches of lift should be the result.

**Congratulations! You have now installed the Baja Grocery Getter Kit!**

You are now ready to take your van to the alignment shop.

